

Telecamera MINI BULLET 5MP 4in1 2,8mm IR 20m DWDR

info@elettronicadefilippo.it

Acquisti online: 081 210318 - Vendita in negozio: 081 450388 - Whatsapp 338 22 89 462

HIKTHCB150M28

6931847156848

Hilook



DESCRIZIONE

- Sensore CMOS 5 MP
- Bullet Exir
- 20 m IR, ICR, 0.01 Lux/F1.2
- 12 VDC, Smart IR, DWDR, DNR, OSD Menu
- IP66, ottica 2.8mm
- Video output HD-TVI/AHD/CVI/CVBS
- Materiale: Metallo

SPECIFICHE

SENSORE IMMAGINE 5 Mpx
high-performance CMOS
RISOLUZIONE 2560 (H) × 1944 (V)
MIN. ILLUMINATION Color: 0.01 Lux @(F2.0,
AGC ON), 0 Lux with IR
SHUTTER TIME PAL: 1/25 s to 1/50, 000 s
NTSC: 1/30 s to 1/50, 000 s
OTTICA 2.8mm
HORIZONTAL FIELD OF VIEW 110°
OBIETTIVO M12
DAY & NIGHT IR cut filter
SINCRONIZZAZIONE Internal
synchronization
FRAME RATE
TVI: 5 M @ 20 fps, 4 M @ 25 fps, 4 M @ 25 fps,
1080p @ 30 fps, 1080p @ 25 fps
AHD: 5 M @ 20 fps, 4 M @ 30 fps, 4 M @ 25fps
CVI: 4 M @ 30 fps, 4 M @ 25 fps
CVBS: PAL/NTSC
AGC Support
D/N MODE Auto/Color/BW (Black and White)
BILANCIAMENTO DEL BIANCO Auto/Manual
AE (AUTO EXPOSURE) DWDR, BLC, HLC,
Global
LINGUA Inglese
FUNZIONI Brightness, Sharpness, Mirror,
Smart IR
VIDEO OUTPUT 1 HD analog output
SWITCH BUTTON TVI/AHD/CVI/CVBS
OPERATING CONDITIONS -40 °C to 60 °C
(-40 °F to 140 °F), humidity: 90% or less
(non-condensation)
ALIMENTAZIONE 12 VDC±25%
POWER CONSUMPTION Max. 4.3W
GRADO DI PROTEZIONE IP66
MATERIALE Metallo
IR RANGE 20 M
COMUNICAZIONE Up the coax, Protocol:
HIKVISION-C (TVI output)
DIMENSIONI Ø 82.6 mm × 69.66 mm (Ø
3.25" × 2.74")
PESO 230g

DESCRIZIONE

- Sensore CMOS 5 MP
- Bullet Exir
- 20 m IR, ICR, 0.01 Lux/F1.2
- 12 VDC, Smart IR, DWDR, DNR, OSD Menu
- IP66, ottica 2.8mm
- Video output HD-TVI/AHD/CVI/CVBS
- Materiale: Metallo

SPECIFICHE

SENSORE IMMAGINE 5 Mpx high-performance CMOS
RISOLUZIONE 2560 (H) × 1944 (V)
MIN. ILLUMINATION Color: 0.01 Lux @(F2.0, AGC ON), 0 Lux with IR
SHUTTER TIME PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s
OTTICA 2.8mm
HORIZONTAL FIELD OF VIEW 110°
OBIETTIVO M12
DAY & NIGHT IR cut filter
SINCRONIZZAZIONE Internal synchronization
FRAME RATE
TVI: 5 M @ 20 fps, 4 M @ 25 fps, 4 M @ 25 fps, 1080p @ 30 fps, 1080p @ 25 fps
AHD: 5 M @ 20 fps, 4 M @ 30 fps, 4 M @ 25fps
CVI: 4 M @ 30 fps, 4 M @ 25 fps
CVBS: PAL/NTSC
AGC Support
D/N MODE Auto/Color/BW (Black and White)
BILANCIAMENTO DEL BIANCO Auto/Manual
AE (AUTO EXPOSURE) DWDR, BLC, HLC, Global
LINGUA Inglese
FUNZIONI Brightness, Sharpness, Mirror, Smart IR
VIDEO OUTPUT 1 HD analog output
SWITCH BUTTON TVI/AHD/CVI/CVBS
OPERATING CONDITIONS -40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
ALIMENTAZIONE 12 VDC±25%
POWER CONSUMPTION Max. 4.3W
GRADO DI PROTEZIONE IP66
MATERIALE Metallo
IR RANGE 20 M
COMUNICAZIONE Up the coax, Protocol: HIKVISION-C (TVI output)
DIMENSIONI Ø 82.6 mm × 69.66 mm (Ø 3.25" × 2.74")
PESO 230g