

TELECAMERA DOME 2MP 4in/1 2.8mm IR 20m DWDR

info@elettronicadefilippo.it

Acquisti online: 081 210318 - Vendita in negozio: 081 450388 - Whatsapp 338 22 89 462

HIKTHCT120M28

6954273663186

HiLook



DESCRIZIONE

- 2 MP high-performance CMOS
- 1920 x 1080 resolution
- 2.8 mm fixed focal lens
- Day/Night switch
- EXIR 2.0, smart IR, up to 20 m IR distance
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP66

SPECIFICHE TECNICHE

SENSORE IMMAGINE 2 Mpx
high-performance CMOS
RISOLUZIONE 1920 (H) x 1080 (V)
MIN. ILLUMINATION Color: 0.01 Lux @(F1.2, AGC ON), 0 Lux with IR
SHUTTER TIME PAL: 1/25 s to 1/50, 000 s
NTSC: 1/30 s to 1/50, 000 s
OTTICA 2.8 mm
HORIZONTAL FIELD OF VIEW 103°
OBIETTIVO M12
DAY & NIGHT IR cut filter
SINCRONIZZAZIONE Internal synchronization
FRAME RATE PAL: 1080p@25fps
NTSC: 1080p@30fps
AGC Support
D/N MODE Auto/Color/BW (Black and White)
BILANCIAMENTO DEL BIANCO ATW/AWB
BLC Support
DWDR (DIGITAL WIDE DYNAMIC RANGE) Support
LINGUA Inglese
FUNZIONI Brightness, Sharpness, DNR, Mirror, Smart IR
VIDEO OUTPUT 1 HD analog output
SWITCH BUTTON TVI/AHD/CVI/CVBS
OPERATING CONDITIONS -40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
ALIMENTAZIONE 12 VDC ±15%
POWER CONSUMPTION Max. 4 W
GRADO DI PROTEZIONE IP66
MATERIALE Metallo
IR RANGE fino a 20 M
COMUNICAZIONE Up the coax, Protocol: HIKVISION-C (TVI output)
DIMENSIONI Ø 82.6 mm x 69.66 mm
PESO 230g

DESCRIZIONE

- 2 MP high-performance CMOS
- 1920 x 1080 resolution
- 2.8 mm fixed focal lens
- Day/Night switch
- EXIR 2.0, smart IR, up to 20 m IR distance
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP66

SPECIFICHE TECNICHE

SENSORE IMMAGINE 2 Mpx high-performance CMOS

RISOLUZIONE 1920 (H) × 1080 (V)

MIN. ILLUMINATION Color: 0.01 Lux @(F1.2, AGC ON), 0 Lux with IR

SHUTTER TIME PAL: 1/25 s to 1/50, 000 s

NTSC: 1/30 s to 1/50, 000 s

OTTICA 2.8 mm

HORIZONTAL FIELD OF VIEW 103°

OBIETTIVO M12

DAY & NIGHT IR cut filter

SINCRONIZZAZIONE Internal synchronization

FRAME RATE PAL: 1080p@25fps

NTSC: 1080p@30fps

AGC Support

D/N MODE Auto/Color/BW (Black and White)

BILANCIAMENTO DEL BIANCO ATW/AWB

BLC Support

DWDR (DIGITAL WIDE DYNAMIC RANGE) Support

LINGUA Inglese

FUNZIONI Brightness, Sharpness, DNR, Mirror, Smart IR

VIDEO OUTPUT 1 HD analog output

SWITCH BUTTON TVI/AHD/CVI/CVBS

OPERATING CONDITIONS -40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)

ALIMENTAZIONE 12 VDC ±15%

POWER CONSUMPTION Max. 4 W

GRADO DI PROTEZIONE IP66

MATERIALE Metallo

IR RANGE fino a 20 M

COMUNICAZIONE Up the coax, Protocol: HIKVISION-C (TVI output)

DIMENSIONI Ø 82.6 mm × 69.66 mm

PESO 230g